



גרין אויל בע"מ
GREEN OIL LTD

Recycled waste oil (LIGHT) specifications

Analysis	Unit	Upper limit	Test Method
Viscosity at 40°C	mm ² /s	1.5	ASTM D 445
Density @ 15.0 c	Kg/m ³ c	0.8	ASTM D1298
Distillation	°C		ASTM D86
10%Evaporated Temp	°C	120	ASTM D86
50%Evaporated Temp	°C	150	ASTM D86
95%Evaporated Temp	°C	190	ASTM D86
F.B.P	°C	230	ASTM D86
Residue	%Vol	1.5	ASTM D86
Loss	%Vol	1	ASTM D86
Total Sulphur	%Wt	700	ASTM D5453
Colour Saybolt	-	25	ASTM D156
Oleffins Content	%Vol	10	ASTM D1319
(Naphthenes + Aromatics) Content	%Vol	40	ASTM D1319

General:

Recycled light waste oil produced by Green Oil is not eligible for excise tax return.

Storage:

- Igniting liquid. Keep away from sources of fire, sparks, static electricity, friction, or any other heat source that could cause a fire.
- Store a fan in place.

Clarification:

At Green Oil Ltd., we take all measures at our disposal and with the utmost effort to ensure that the above information is accurate and correct as of the date of the last update of this document. However, it should be noted that the above information may be affected by post-print changes, changes in the production formula or method of application of the product. Therefore, we recommend that you verify the up-to-date information before using the product.

For more information: For questions and clarifications, please contact our company at +972-3-9366644, fax +972-3-9080453 or by email: info@newgreenoil.com

Release: 03 Publication date : September 2022

 03-9366644

 03-9080453

 Hasahlav St. 15, I.A. Ariel West

 P.O. 4005 Ariel, zip 4070006

 www.newgreenoil.com